

KL1/B/P

Dynamic
loudspeaker with
volume control

Article-No.:
6601-001-000-51



LOUDSPEAKER - KL1/B/P

Product:

Characteristics

- Very rugged plastic housing
- Integrated potentiometer on the back for controlling the volume
- Small design for easy installation
- Frequency range optimized for radio communication
- Flexible mount

Application range

- For mobile and fixed radio systems

Accessories

- KL1 spare parts set (mount and knurled screw)

Scope of delivery

- Loudspeaker with integrated volume control, cable and mount

Technical Data:

General

Housing:	Plastic PA, black
Dimensions:	Height 72 mm, Width 80 mm, Depth 50 mm Ø 58 mm
Weight:	250 g (8.8 oz)
Connection:	2-wire cable 2.00 m, without connector, open wires
Storage temperature:	-30 °C to +75 °C (-22 °F to +167 °F)
Operating temperature:	-25 °C to +60 °C (-13 °F to +140 °F)

Loudspeaker

Frequency range:	300 Hz to 6 kHz at -10 dB
Effective sound pressure:	81 dB/W/m ± 3 dB at 1 kHz
Impedance:	8 Ω ± 20 % at 1 kHz
Maximum output:	max. 5 W
Potentiometer:	Attenuation: 0 dB to 22 dB