

PS12 USB

Desktop microphone
with dynamic
microphone and
USB connection

Article-No.:
6401-003-001-40



Product:

Characteristics

- Dynamic unidirectional high noise canceling gooseneck microphone
- Device recognized as external sound card by the computer
- Buttons and LEDs recognized as HID (Human Interface Device)
- Compatible with Microsoft® Windows® Vista, Windows® 7 and Windows® 8

Options

- Black matte housing (Art.-No.: 6401-003-001-41)

Application Range

- PC-based control centers in fixed indoor applications

Accessories

- WS16 windscreen (Art.-No.: 6401-003-001-41)

Scope of Delivery

- Desktop microphone with USB cable
- Printed manual

Technical Data:

General

Microphone head:	Brass, sand blasted chrome (matte)
Gooseneck:	Metal, matte silver coated
Housing:	Metal, matte silver coated
Dimensions:	Microphone head: Length 80 mm, Ø 24 mm Gooseneck: Length 200 mm, Ø 11 mm Housing: Height 32 mm, Width 105 mm, Depth 160 mm
Weight:	770 g (27.1 oz)
Connection:	2 m cable with USB-A plug
Operating and display elements:	1 Button, black 1 LED, blue
Storage temperature:	-30 °C to +70 °C (-22 °F to +158 °F)
Operation temperature:	-10 °C to +55 °C (-14 °F to +131 °F)

Microphone

Frequency range:	150 Hz to 12 kHz at -10 dB
Directivity:	Cardioid (at 1 kHz; 180° -20 dB)